



Zone valve

benefits

- Robust brass version
- Fully tight
- Intuitive position indicator using a coloured traffic light system
- low pressure loss, ideal for large water volumes
- Easy integration into heat pumps or hydraulic systems
- maintenance-free



Application

For integration into heat pumps or hydraulic systems. AZV can be used, for example, to switch between the operating modes "heating" and "cooling" or "heating" and "service water heating" as well as for switching over in water storage tank applications and is also suitable for shutting off. Different housing versions allow the zone valve to be customised to suit the application and location. Suitable for water and water/glycol mixtures with up to 50 % glycol.

Description

Zone valve consisting of valve unit and electrical drive. The proven, robust design results in complete tightness with low pressure loss. A position indicator with a coloured traffic light system intuitively signals the switching state of the valve. The direction of flow of the valve in the rest position can be changed while the valve is installed, without the necessity to open the water circuit. Manual emergency operation is possible by removing the electric motor and turning the integrated hand wheel.

Technical Specifications

Valve

Material

Housing: brass (CW617N)
seals: EPDM

Connections

see table

Operating pressure

max. 10 bar

Differential pressure

max. 2 bar

Setting angle

90 °

Medium

Heating circuit water or water/glycol mixture (glycol max. 50 %)

Electrical drive**Housing**

Material: plastic (PC/ABS)

Protection class: II

Degree of protection: IP 54 (EN 60529)

Electrical connection

AMP Superseal 1.5 Series 1745082-1

Term

15 seconds

Power input

< 7 W, in rest position 0 W

Options

- Actuator with other adjustment times
- Drive with more powerful motor/gear
- customised housing geometry
- other connections

Operating temperature range

Medium: -20/+90 °C

Ambient: 0/75 °C

Supply voltage

AC 230 V, 50 Hz

Nominal duty type

S3 25 %

Option

- Actuator with other adjustment times
- Drive with more powerful motor/gear
- customised housing geometry
- other connections

Versions

			Part no.
Zone valve AZV 442	2-W G $\frac{3}{4}$ NC		81440
Zone valve AZV 443	2-W G1 NC		81441
Zone valve AZV 452	2-W G $\frac{3}{4}$ NO		81442
Zone valve AZV 453	2-W G1 NO		81443
Zone valve AZV 642	3-W G $\frac{3}{4}$		81444
Zone valve AZV 643	3-W G1		81445
Zone valve AZV 647	3-WE G1		81446
Zone valve AZV 844	3-W G1 $\frac{1}{4}$		81447

 in-stock items

 Non-stock items