



level probe LS 300 EU

Part no. 53300

level probe LS 300 EU for overfill prevention system LS for Ex (WHG)

benefits

- approved as part of an overfill prevention system as per German WHG together with level transducer LS 500
- self-monitoring with automatic corrosion monitoring
- all wetted parts made of stainless steel 316 Ti
- suitable for use in liquids with an overpressure of 3 bar
- Ex approval

Application

Level probe for transducers as part of an overfill prevention system for stationary and stationary-use tanks. Suitable for installation in all tank versions. Approved without list of substances for water-polluting liquids, also with flash point < 55 °C.

Description

Approved part of an overfill prevention system according to WHG together with the LS 500 transducer – self-monitoring and with automatic corrosion monitoring. LS 300 EU consists of a height-adjustable probe tube with a PTC thermistor sensor element at the bottom end, screw fitting and a junction box with integrated overvoltage protection. Standard length 500 mm, max. length 3,000 mm. The level probe can be used in flammable liquids up to 3 bar overpressure.

Technical Specifications

Material

junction box: brass, chrome-plated
 Probe tube: Stainless steel 316 Ti
 Screw fitting: Stainless steel 316 Ti
 PTC thermistor: stainless steel-encapsulated

Process connection

Einschraubgewinde G $\frac{3}{8}$

Operating temperature range

Medium: -25/+50 °C

Degree of protection

IP 67 (EN 60529)

approval

DIBt: Z-65.11-228

EU type examination certificate

TÜV 00 ATEX 1656X Ex II 1G Ex ia IIC T4 und Ex II 1/2G Ex ia IIC T4

Versions

	Length	Length		Part no.
level probe LS 300 EU	500 mm			53300

-  in-stock items
-  Non-stock items