



Anti-tamper cap valve G $\frac{3}{4}$ x G $\frac{3}{4}$

Part no. 77924

anti-tamper cap valves

benefits

- integrated drain valve with hose connection - easy operation via standard square spanner AF 5 for radiator vent valves
- with shut-off valve which can be secured against inadvertent closing by means of a lead seal

Application

For connection, maintenance and checks of diaphragm expansion vessels in heating systems as per EN 12828 and in solar systems. To be installed at the water inlet of the expansion vessel.

Description

Anti-tamper cap valve with screw connection G $\frac{3}{4}$ x G $\frac{3}{4}$ or G1 x G1. The shut-off valve is secured against inadvertent closing by means of a cap and a lead seal. Valve operation via standard square spanner size 5 for radiator vent valves. The expansion vessel can be shut off from the heating system and drained via the drain valve for the required function test or for replacement.

Technical Specifications

Operating pressure

max. 10 bar

Operating temperature range

Medium: 0/120 °C

Connections

Inlet x outlet: x G $\frac{3}{4}$

Drain capacity

Anti-tamper cap valve with drain valve
0.5 m³/h

Versions

			Part no.
Anti-tamper cap valve G ³ / ₄ x G ³ / ₄	with drain valve		77924

- in-stock items
- Non-stock items