



## Temperature and humidity sensor FTM 20 TF

**Part no. 61255**

**Temperature and humidity sensor**

### benefits

- Maintenance-free battery-less operation
- Solar-operated energy storage module for several days of operation even in darkness
- Either easy adhesive mounting or placement by means of base
- Battery operation optionally possible
- EnOcean® wireless technology

### Application

Wireless sensor for determination of the ambient temperature and air humidity at a defined location and transmission to AFRISOhome gateway.

### Description

The temperature sensor FTM 20 TF measures the ambient temperature and the humidity at regular intervals. Significant changes of the sensor data are immediately transmitted to the AFRISOhome gateway; they can be used as parameters to control actuators such as the radiator actuators AVD 30 or extractor fans with EnOcean wireless technology.

The energy required to send a wireless telegram is generated by means of the integrated photovoltaic cell. The integrated energy storage module allows for several days of operation even in total darkness. In permanently dark environments (such as basements or warehouses) it is also possible to use a button cell battery.

A double-sided adhesive strip allows for extremely easy mounting of the compact housing to walls or furniture. It is possible to plug on a metal plate which serves as a base for placing the sensor on a shelf, a window sill or a sideboard.

The AFRISOhome gateway in conjunction with additional AFRISO smart home products with EnOcean® wireless technology allows the user to configure a whole range of fully customisable, extensible applications.

### Technical Specifications

#### Operating temperature range

Ambient: -20/+60 °C

#### Measuring range

temperature: -20/+60 °C

Accuracy: ± 0.5 K

Humidity/moisture: 0/100 % rH

Accuracy: ± 4.5 % rH

#### Supply voltage

Energy harvesting (via photovoltaic cell)

CR1225 button cell

**Housing**

Colour: white, similar to RAL 9010  
 W x H x D: 76.2 x 22 x 15 mm  
 Weight: 20 g  
 Degree of protection: IP 40 (EN 60529)

**EnOcean® wireless**

FTM 20 TF  
 A5-04-03  
 Frequency: 868.3 MHz  
 Transmission power: max. 10 mW  
 Range: 10 – 30 m  
 Range: depending on room arrangement and materials in the building

**Scope of delivery**

- Temperature sensor
- Cap triangular or quadrangular
- Base
- 1 x adhesive tape/wall bracket
- without battery

**necessary additional components**

- AFRISOhome gateway

**Versions**

Part no.

Temperature and humidity sensor FTM 20 TF	●	61255
--	---	-------

- in-stock items
- Non-stock items