



## Flue gas analyser BLUELYZER ST set Pro

Part no. P00131

Complete package flue gas analysis

### benefits

- CO high device for measurements at all heat generators up to 20,000 ppm, including pellets boilers
- comprehensive all-rounder set with IR printer
- Combustion air probe for measurements at room air-independent systems
- robust hard top case
- the world's smallest, fully-featured HVAC all-rounder with TFT colour display
- Flue gas analysis, pressure measurement (draft) and (differential) temperature measurement with a single instrument
- CO ambient measurement with two freely adjustable alarm thresholds
- fully-fledged temperature measurement program, differential temperatures (e.g. flow/return) can also be determined
- Hold function: Display shows the measured value for a given period of time while the measurement keeps running in the background
- Measurement programs and measured values can be freely edited
- display reverse function: TFT display can be rotated by 180° for easy reading and excellent working conditions at the point of measurement
- zoom mode for entire display, "Single-value display"
- Memory function with up to 100 measurement logs
- CAPBs®-enabled



### Application

Ideal for HVAC professionals for accurate adjustments or inspections, on par with official flue gas analysers. BLUELYZER ST is suitable for flue gas analysis, pressure measurement and (differential) temperature measurement. The HVAC all-rounder also provides exact calculation of the Eta value for all condensing heating systems with fuel-specific dew point calculation.

## Technical Specifications

**Flue gas temperature/differential temperature**  
0/1150 °C

**Air temperature/combustion air temperature**  
-20/+200 °C

**Draft**  
-70/+70 hPa

**O<sub>2</sub> measurement**  
0/21 Vol.-%

**CO measurement**  
nominal: 0/20000 ppm

**Indication (calculated values)**  
CO<sub>2</sub>, CO<sub>undiluted (air-free)</sub>, Lambda, Dew point, Eta efficiency, Flue gas losses qA, CO mg/m<sup>3</sup> (natural gas), CO mg/kWh (fuel oil)

**Operating temperature range**  
Ambient: 0/40 °C  
Storage: -20/+50 °C

**Dimensions**  
W x H x D: 66 x 143 x 37 mm

**Degree of protection**  
IP 42 (EN 60529)

**Display**  
TFT colour display 2.8 "  
W x H: 45 x 60 mm  
240 x 320 pixels

**Connections**  
Draft/pressure: Ø 7 mm  
Gas: Ø 8 mm  
temperature: socket type K

## Versions

	Part no.
Flue gas analyser BLUELYZER ST set Pro	P00131

 in-stock items

 Non-stock items