



Flue gas analyser EUROLYZER® S1 set Basic

Part no. P00140
Flue gas analyser

benefits

- Configurable macros for practical multi-measurement of, for example, partial load, full load and annular gap
- Compact flue gas probe AKS-K 170 mm with draft connection
- large high-resolution display for optimum readability and and intuitive menu navigation, protected by scratch-resistant glass
- Pioneering "dual-mode concept": Intuitive one-hand operation via scroll wheel or touch display – sensitive even with work gloves
- Ready for all typical HVAC measuring tasks thanks to Bluetooth® connection to more than 35 sensor modules and sets of the CAPBs® system
- TÜV-tested measurement as per 1st and 44th BlmSchV (German Federal Immission Act)
- NO sensor can be retrofitted
- H₂-compensated robust CO sensor (measuring range up to 10,000 ppm)
- Multi-memory: Combine up to six different measurements into a single measurement report (for example, full load measurement/partial load measurement or flue gas measurement and flow pressure measurement)
- Data transmission via Bluetooth® or QR code to the AFRISO app EuroSoft® connect for on-site documentation
- 5 years warranty on O₂ sensor
- 7 years full warranty in connection with a service contract



Application

Designed for flue gas measurements at oil, gas and pellets fired systems as well as for tightness tests at gas lines, for checking the connection pressure/flow pressure and the pressure loss. TÜV-tested measurements as per 1st and 44th BlmSchV (German Federal Immission Act) can be performed reliably and intuitively. Fast and easy Bluetooth® connection to more than 35 sensor modules and sets of the AFRISO CAPBs® make EUROLYZER® S1 the central controller for all HVAC tasks.

Technical Specifications

Flue gas temperature/differential temperature
0/1150 °C

Air temperature/combustion air temperature

-20/+200 °C

Draft

-70/+70 hPa

O₂ measurement

0/21 Vol.-%

CO_{H2} measurement

nominal: 0/4000 ppm

maximum: 0/10000 ppm

Indication (calculated values)CO₂, CO_{undiluted (air-free)}, Lambda, Dew point, Eta efficiency, Flue gas losses qA, CO mg/m³ (natural gas), CO mg/kWh (fuel oil)**Operating temperature range**

Ambient: 0/40 °C

Storage: -20/+50 °C

weight (measuring instrument)

500 g

Dimensions

W x H x D: 80 x 218 x 44 mm

Degree of protection

IP 40 (EN 60529)

Display

high-resolution display 4.3 "

Connections

Draft: Ø 7 mm

Gas: Ø 8 mm

temperature: 2 x socket type K

Versions**Supply voltage**

lithium-ion battery (3.6 V/5000 mAh)

Power supply unit (USB-C)

Battery or mains

Hours of operation (eco mode)

12 hours

Data memory

internal memory, 10000 Messungen

Interfaces

Infrared,

Bluetooth®,

QR code generator,


USB-C

ApprovalsTÜV-tested as per 1st and 44th BImSchV,
DIN EN 50379-1/2**Scope of delivery**

- Flue gas analyser EUROLYZER® S1 (O₂, CO/H₂+, draft)
- with integrated magnet in housing
- Calibration report
- Power supply unit NTE 5 USB-A
- charging cable USB-A to USB-C (1 m)
- 5 x Infiltec fine filter
- 5 x Teflon membrane
- Condensate filter cartridge KFP
- Flue gas combination probe, compact, AKS-K FZ 170 mm
- ambient air probe TFB-UL 50-1
- system case L "Gas analysis"

Part no.

Flue gas analyser EUROLYZER® S1 set Basic	O ₂ , CO/H ₂ +, draft	●	P00140
--	---	---	--------

 in-stock items Non-stock items