



Boiler water low level alarm WMS-WP6-R2

Part no. 42319

Boiler water low level alarm WMS-WP6 - mechanical

benefits

- for protection of the boiler when the water level is too low
- TÜV-tested as a water level switch
- Direct mounting via welding socket or connection thread
- with test key for function test

Application

For sealed heating systems to protect the boiler as per EN 12828 in the case of low water levels.

Description

Mechanical boiler water low level alarm with float. Consisting of a cast brass body with welding sockets and a float mechanism, an electrical switch, test and unlock buttons. TÜV-tested as a water level limiter. If the water level in the boiler drops below a minimum level, a float activates a switch. The power supply to the boiler is interrupted. A locking mechanism keeps the burner from switching back on automatically. The test button allows the float to be lowered to simulate a low water alarm condition.

Version WMS-WP6-R2 with male connection thread R2 for direct installation in the boiler.

Technical Specifications

Operating temperature range

Medium: max. 120 °C

Ambient: max. 70 °C

Housing

Probe body: cast brass

WMS-WP6-R2

271 mm

Degree of protection: IP 54 (EN 60529)

Float

Plastic

Connection

WMS-WP6-R2

male thread R/2

Operating pressure

max. 10 bar

Test pressure

15 bar

Contact rating


AC 250 V, 6 (2) A

type approval mark

TÜV.WBH.yy-232

"yy" represents the year of the approval

Technical Drawings



Versions

Part no.

Boiler water low level alarm
WMS-WP6-R2

with connection thread R2 male



42319

- in-stock items
- Non-stock items